

# Korogard® Caulk

## PRODUCT DESCRIPTION

**KOROSEAL** Wall Protection Systems provides an acrylic-based evaporative cure sealant with a special silicone modifier that is color-matched to **KOROGARD** Wallcovering standard colors. **KOROGARD** caulk is packaged in 10.5 oz. cartridges.

## PRODUCT USES

**KOROGARD** caulk will help provide a **KOROGARD** Protective Wallcovering installation with a finished appearance. **KOROGARD** caulk may be used as an alternative to moldings for inside corners and for the expansion gap between sheets. **KOROGARD** caulk will still allow for the normal thermal expansion of **KOROGARD** Wallcovering when extruded into the required 1/16" (1.59mm) gap. When applied properly, **KOROGARD** caulk will provide waterproof seam treatment.

## INSTALLATION

Surfaces should be free of oils, dust, old caulking, or other contaminants. **KOROGARD** caulk may be installed between temperatures of 65°F and 85°F (18°C and 29°C). The caulk darkens to color-match as it dries. A 10.5 oz. tube of caulk provides approximately 150 linear feet of coverage. Joint dimensions should not exceed 3/8" x 3/8" (9.53mm x 9.53mm). Tooling is recommended immediately after application to ensure firm contact with joint interfaces. Hands and tools should be cleaned with soapy water before the caulk dries.

## SPECIFICATION

Color-matched caulk shall be provided by **KOROSEAL** Wall Protection Systems. The caulk shall be acrylic-based with a silicone modifier. The caulk shall have the same color number as the **KOROGARD** Wallcovering. Specification typically falls under Section 3.2 Part B.

The suggestions and data in this document are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.



800-628-0449 • [www.korogard.com](http://www.korogard.com) • Division 10 26 00